

Implement Efficient Route Discovery of Broadcasting Technique in Moving Object Detection and Tracking

Mahalingam Thangaraj
Sathyabama University
India
mahaaalingam@gmail.com



ABSTRACT: Generally the surveillance system wireless camera is used to monitor the object in heavy traffic in secured way and it also support satellite communication to broadcast the tracked object information to others. It is used to reduce computational delay in real time detection and tracking videos. In object detection and tracking system detection and background separation is very important role, here powerful ruling camera is used to increase the algorithm time complexity compared to normal tracking system. In this paper we propose competent CAMSHIFT algorithm which is both Normalized cross correlation and mean shift algorithm's combination. By the usage of this competent CAMSHIFT object tracking techniques is used to track the object that we need to focus depending on the internal features of the object in non ideal environment. Here we propose cloud environment which incorporate a distinct dynamic effective broadcasting algorithm which renders efficient way to share the information extraordinarily without loss of information during their transmission to destination. While broadcasting if there is collision to find the alternate path to the broadcasting procedure else continue broadcasting the information. In case cloud server fails to get acknowledgement in predefined time i.e timer runs out then it calls shortest path first algorithm to find alternate route to compensate the server failure. It also supports high secured data transmission between end users, so as to achieve the real time detection and tracking of an object that is moving which is processed by OPENCV/MATLAB.

Keywords: Wireless Camera, Moving Object Detection, Object Tracing, Broadcasting

Received: 28 August 2017, Revised 4 October 2017, Accepted 10 October 2017

© 2018 DLINE. All Rights Reserved

1. Introduction

An essential computer vision building block is tracking of humans. It is needed for many applications aligning from military and surveillance passing by computer aided driven as well as human machine interfaces which is advanced. Human tracking's main challenges include 1). Distinguishing between foreground and background area, 2). Distinguishing objects that are tracked objects and objects that are on the equal scene, 3). Features of the objects that are tracked to transform which is caused by changes in lighining, 4). Tracked objects two dimensional scaling to the scenes in which the object changes their distance from

the camera, 5). Tracked objects occlusion by other objects. We devised the concluding tracker, which has a color histogram never ending adaptive mean shift tracker OpenCV oriented implementation, where instead of a box histogram by using a masked histogram. The tracked histogram accuracy has been improved. The user is interactively allowed to position a template which is predefined on the starting human being tracked calculate the mask and making of gray scale growing of the region and the foreground and background are separated (3) To find the methods of background and foreground areas. The standard mean shift tracker and the tracker has been compared where for a selected region, and the starting histogram is relied upon calculating the box histogram.

In a single window the trajectory of moving objects are converged, and there is a frame apply the partitioning algorithm to partitioning the converged object (4). Here we apply the clustering algorithm after partitioning the trajectory data. On getting the result of Normalized Cross Correlation of two consecutive frames in the sequence of images, Normalized Cross Correlation algorithm depends. To finding out the similarity between the two frames correlation is basically used. Normalized Cross Correlation value is highest when consecutive frames are similar. If it is the situation the moving objects means the both consecutive frames are not similar, with regard to pixel values, if that is the result we use Normalized Normalized Cross Correlation is based on finding the cross correlation between two consecutive frame in their sequence of images. To find the similarity between two Cross Correlation.

2.1 Related Works

2.1 Segmentation of an Image

In the view of computer technology the basic utility is the color application, that has content based retrieval of image for libraries of multimedia founding of skin (1), object gratitude (2), and robot organization (3), hence in this previously four kinds of approaches are discussed and categorized it. which has merge and split algorithm(10) edge detection which has color variant snake usage(4) last one is the segmentation based on physics. The methods and application of color segmentation shown in (5) On pixel clustering in aspect space using parametric density approximation the dealing to segmentation of an image adopted to relied work. In the precedent the clustering subject or learning that is unsupervised (6). The notice and the clustering technique that is used which is existing before that is not the same kind (7). whatever so on the purpose of acceptable criteria for illumination the precise clustering more of the work in this space has been analyzed(8) using many methods of data perfectness the system follows self generating depiction systems(6). elucidating the exact and needed size for a peak in which is featured by taken as governing self cluster in terms of explaining the necessary size for a peak in space which is featured by taken as self governing in which image is blur and it is original.

The moving object detection is crucial in a multitude of defence and security applications in which detecting target is accomplished for target tracking as well as self acting target recognition, identification (9, 10, 11, 12, and 13) and classification. Tracking the target at the information which is furnished at lower level (LLIF) is deployed in the information fusion which is high in level (HLIF), case area surveillance (14) consciousness and user monitoring, in HLIF there are many challenge which includes semantic knowledge, management and representation of information(15,16). There is a necessity for the performance improvement that can be aided by other sensors for robust detection and tracking, video's that are for surveillance usage application have outdoor videos whose standard bright be degraded. Other sources that are noisy which includes turbulence atmospheric that are sensor platform scintillation etc. For handling the videos quality for movement detection approaches from original image, such as sensing approach which is layered(17), non fusion of image (18,19) and use of descriptors (20). Object that are moving may be very small which occupies only few pixel, that makes detection the target very challenging which is seen in wide area motion imagery (21). In this condition the approaches which exist may produce many amounts of false alarms of things to be detected which are not actually the aim.

Tracking target has been investigated rapidly as illustrated in survey papers (22, 23). This paper has the extension of optical flow techniques (24, 25, 26). Most of the development in tracking the video are from videos which is their indoor with objects that are large level scenes which is outdoor research should focus on lighting perspective and variation in observation. Optical flow based approaches, one of the major techniques is used for target detection and it is widely used Gunnar farneback (GF) methods (28) and Lucas Kanade (LK) method (29, 30, 31). are the two earliest methods of start computation of optical flow in computer vision. On two frame difference algorithms these both are as LK technique needs the pyramid construction updating model in square feature scale space and iterative computational at constructively better scales, we closely look at the GF technique for a computation which is dense optical flow in the frame work.

Image processing and multisensory system, cloud technology has indeed become very significant (32, 33, 34).. Framework which is based on cloud uses cloud computing (35). A maintainer the cloud would take decision on the fast arrangement of computing resources, so as to reach the end result of performance of users. Inside the cloud , there are more virtual machines that runs on all physical machine. All the VMs are fit for running variety of detection and tracking algorithms.

Normally one registration algorithm is run by several threads, more than one or one VMs. Other signification of infrastructure of cloud computing is that , the pace of the process is improved highly by the parallel implementation resource which is elastic , usage of computation of the cloud till recent days, exact experiments were processed for tracking the video application informed in literature mainly for the involvement of constant conditions of lighting as well as equally stable image collections.

3. System Model In Object Detection, Tracking And Broadcasting Algorithm

3.1 Competent Camshift Tracking Algorithms

The color that can be tracked using color histogram through color probability distribution image and converted the unprocessed image in each frame of video. To find centre and size of the color object which is used by the competent CAMSHIFT algorithm. To find next video image reported the current window size and tracked object location through to fix the search window. To continual the tracking process uninterrupted. The simplification of algorithm that is algorithm of mean shift is denoted with gray color.

3.2 Competent Continuously Adaptive Mean Shift Tracking Algorithm

Any problem could happen if HSV values are used, and with distinct pixel values. If clarity is less(v near 0), the same condition for saturation. 1+ve then that ends up in bearing, as in a small hex cone, the lesser values of discrete here pixels won't stand minor modification in RGB satisfactorily. In hue values, it leads to natural swings to break this problem, pixels of very low accordance brightness values should be treated not in the exactly it should be treated , which signifies the camera should be adjust automatically or be adjusted for heavy brightness or it cannot be tracked dim scene. While color that is bright can take or a flesh with sunlight, therefore we can use even an upper threshold for disregarding hue pixel that is flesh accordance which is maximum. Here it is undefined at very low saturation so rejected pixels which are extremely less in accordance saturation.

The competente camshift algorithm with cloud

Is shown in Figure1 Fix a search window dimension

1. Fix search window's foremost position
2. In the search window work out the mean position.
3. The search window has to be centered in mean position calculated in step 3
4. Redo steps 3 & 4 till assemblage (or till the mean position travels lesser threshold which is preset)
5. Read two consecutive frames as a present frame & previous frame from the image succession.
6. Divided four quadrants in that frames.
7. For ex. Divided current frames are of 4 parts called as X1, X2,X3 & X4
8. For every sub image of current frame with their previously frame, that find out the NCC.
9. Now identify least measure value of NCC from these four values.
10. Apply the threshold to this minimum value of NCC. By taking average of four NCC value the threshold value is selected.(ie C1, C2, C3 & C4)
11. For instance, if the moving object present in first quadrant, the least measure value of NCC is acquired at the first quadrant
12. Now work the initial quadrant the disparity among the initial quadrants of two successive segments has to be taken.
13. Then by performing using mean shift algorithm find the position of moving object.
14. Carry out the Centroid computation and find the moving object centroid




Figure 1. System Model In Object Detection, Tracking in cloud Environment

15. Then the second least measure value from the C1 through C4 is acquired. This is made to inspect if any other object in motion is existing in further part of an image.

16. When the next least measure value is above the minimum limit, it suggests the object in motion is present in that quadrant. Now track the object by identifying the position of second moving object.

17. The moving object has to be tracked at the end using CAMSHIFT algorithm

18. The same system has to be recurring for the next frame.

3.3 NCC(Normalized Cross Correlation)

In equation (1) A and B, \bar{A} and \bar{B} shows average value of pixel, r is regularized with regard to all corresponding images and it continually falls in the range (-1,1). Correlation is used for assessing analogy of two images. In component identification and

notarization it is useful. The following equation gives the Normalized cross correlation in equation (1).

$$r = \frac{\sum_m \sum_n (A_{mn} - \bar{A})(B_{mn} - \bar{B})}{\sqrt{\left(\sum_m \sum_n (A_{mn} - \bar{A})^2\right) \left(\sum_m \sum_n (B_{mn} - \bar{B})^2\right)}} \quad (1)$$

In figure 2. foundation steps concerned in the procedure are shown .as it depicts from the static camera input image sequence is taken in to four quadrants in two continuous frames from the image sequences are partitioned. After getting the Normalized Cross Correlation among two divided segments the object in motion detection takes place ,detection of object which is moving video check the occurrence of an object in the list of an image and possible pointing it exactly for identification. If the position when start to object in motion is acquired by carrying out component related analysis .By assessing the centroids of which is perceived objects in motion, detected moving objects tracking takes place. Tracking causes the target detection over the period, thus creating its route. Object tracking's aim is to establish a correspondence between objects of intention is forming a similarity among objects of parts of objects in sequential segments and to remove time-based information on objects such as posture route direction.




Figure 2. Foundation steps

A Novel Broadcasting Algorithm In Object Tracking

- Step 1: Initiate the process
- Step 2: Call procedure broadcasting
- Step 3: If no collision in broadcasting
- Step 6: Notify unique id of the server
- Step 7: End If
- Step 8: If cloud sent for the first time Then
- Step 9: 'msg' Forwarded
- Step 10: Else




Figure 3. Energy Efficient Architecture For Detection And Tracking Object Using Cloud Broadcasting.

Step 11: Decline the forward process

Step 12: End If

Step 13: If server receives tracking msg== first time Then

Step 14: Create a new list

Step 15: Else

Step 16: Modify previous list (msg)

Step 17: End If

Step 18: Remove existing msg by previous

Broadcasting node

Step 19: If (tracking of msg in head of the queue) Then

Step 20: Broadcast successfully

Step 21: End If

Step 22: Else

Step 23: Quit the process until tracked msg at the head of the list
 Step 24: End If
 Step 25: Goto step 40
 Step 26: Else
 Step 27: Call procedure broadcasting
 Step 28: If cloud does not receive acknowledgement predefined time from the server then
 Step 29: To identify any one of the server failure
 Step 30: Else
 Step 31: To determine the shortest path
 Step 32: Call procedure shortest path algorithm
 Step 33: To select the secondary path for broadcasting
 Step34: Rebroadcasting data packet
 Step35: Update route in routing table
 Step36: Notify unique id of the server
 Step 37: Goto step 13
 Step 38: Else
 Step 39: Quit the process until tracked msg at the head of the list
 Step 40: End
 Step 41: Stop.

4. Results and Discussion

In figure 3. Cloud is at first starts the broadcasting of specific object information to all the servers involved. If specific object information is broadcasted to all the servers, all servers execute the detection and tracking process simultaneously. While broadcasting if there is collision to find the alternate path to the broadcasting procedure else continue broadcasting the information. If any of the server tracks the specific object then it can immediately communicate all other server and cloud to transfer the tracked specific object information. So remaining server can stop tracking the specific object because the server has found it already. If server finds the tracking message for the first time it then creates the list otherwise it can append the message by modifying the previous message. If head of queue has the tracking message then the broadcast is successful else it calls itself recursively until head has tracking message at its start. Then procedure can be stopped. In case cloud fails to get acknowledgement in predefined time i.e timer runs out then it calls shortest path first algorithm to find alternate route to compensate the server failure. Using this procedure, new route is found and updated in the routing table. Now the process can be initiated again and if broadcast is successful then it is terminated. In figure (4) (a) and (b) shows the tracked object information.




Figure 4. (a) (b)

5. Conclusion and Future Work

The role of object detection and tracking system is very important in Digital image process. In this paper we implemented an algorithm competent CAMSHIFT, which is drastically reduce the time complexity and improve the quality of service in extreme level. The tracked objects are successfully interact with cloud and which in turn broadcast to other server without any time delay and overcome the problem of ambiguous process of already tracked object. In future We try to incorporate any cryptography techniques for secure the data while broadcasting using cloud environment. The architecture focus to extract the perfect object which is captured for the process. The cloud which in turn broadcast the captured object rest of the server using broadcasting approach. But still we found security issues in data broadcasting techniques. So overcome the above issues in future we try to incorporate cryptography techniques in tracking procedures.

References

- [1] Fang, Y., Tan, T. (2000). A Novel Adaptive Colour Segmentation Algorithm and its Application to Skin Detection, *In: Proc. BMVC 2000*, p.23-31. BMVA.
- [2] Finlayson, G. D., Tian, G. Y. (1999). Colour Normalisation for Colour Object Recognition, *International Journal of Pattern Recognition and Artificial Intelligence*, p. 1271-1285.
- [3] Skarbek, W., Koschan, A. (1994). Colour Image Segmentation , A Survey. *Technischer Bericht 94-32*, Technical University of Berlin.
- [4] Gevers, T., Ghebreab, S., Smeulders, A.W. M. (1998). Colour Invariant Snakes, *In: Proceedings BMVC 1998*, p 578-588. BMVA, 1998.
- [5] Klinker, G. J., Shafer, A., Kanada, T. (1990). A Physical Approach to Colour Image Understanding, *International Journal of Computer Vision*, 4, p. 7-38, 1990
- [6] Thacker, N. A., Abraham, I., Courtney, P. (1997). Supervised Learning Extensions to the CLAM Network, *Neural Networks*, 10 (2) 315-326.
- [7] Hnin Su Khaing., Thein, Thandar. (2014). An efficient clustering algorithms for moving object trajectories, *In: 3rd International Conference on Computational Techniques and Artificial Intelligence (ICCTAI'2014) Feb. 11-12, 2014 Singapore*.
- [8] McArdle, G., Tahir, A., Bertolotto, M. (2012). Spatio-Temporal Clustering of Movement Data: An Application to Trajectories Generated by Human- Computer Interaction, *ISPRS Annals of the Photogrammetry, Remote Sensing and Spatial Information Sciences*, Volume I-2, 2012, XXII ISPRS Congress, 25 August – 01 September, Melbourne.
- [9] Blasch, E., Hong, L. (1998). Simultaneous Feature-based Identification and Track Fusion, *In: IEEE Conf. on Dec. Control*, p. 239-245.
- [10] Blasch, E. (1999). Derivation of a Belief Filter for Simultaneous High Range Resolution Radar Tracking and Identification, *Ph.D. Thesis*, Wright State University.
- [11] Connare, T. *et al.* (2001). Group IMM tracking utilizing Track and Identification Fusion, *In: Proceedings Workshop on Estimation, Tracking, and Fusion; A Tribute to Y. Bar Shalom*.
- [12] Blasch, E., Kahler, B. (2004). Multiresolution EO/IR Tracking and Identification, *In: Int. Conf. on Info Fusion*.
- [13] Blasch, E., Yang, C., Kadar, I. (2014). Summary of Tracking and Identification Methods, *In: Proc. SPIE*, 9119.
- [14] Blasch, E., Bosse, E., Lambert, D. (2012). *High-Level Information Fusion Management and Systems Design*, Artech House, Norwood, MA.
- [15] Blasch, E. P., Lambert, D. A., Valin, P., Kokar, M. M., Llinas, J., Das, S., Chong, C-Y., Shahbazian, E. (2012). High Level Information Fusion (HLIF) Survey of Models, Issues, and Grand Challenges, *IEEE Aerospace and Electronic Systems Mag.*, 27, (9) September 2012.
- [16] Blasch, E., Steinberg, A., Das, S., Llinas, J. *et al.* (2013). Revisiting the JDL model for information Exploitation, *In: Int'l Conf. on Info Fusion*.
- [17] Mendoza-Schrock, O., Patrick, J. A. *et al.* (2009). Video Image Registration Evaluation for a Layered Sensing Environment, *Proc. IEEE Nat. Aerospace Electronics Conf (NAECON)*.

- [18] Wu, Y. *et al.* (2011). Multiple Source Data Fusion via Sparse Representation for Robust Visual Tracking, *In: Int. Conf. on Info Fusion*.
- [19] Liu, Z., Blasch, E., Xue, Z., Langanieri, R., Wu, W. (2012). Objective Assessment of Multiresolution Image Fusion Algorithms for Context Enhancement in Night Vision: A Comparative Survey, *IEEE Trans. Pattern Analysis and Machine Intelligence*, 34 (1) 94-109.
- [20] Wang, C., Li, S., Shen, Y., Song, Y. (2014). Evaluation of Feature Detectors and Descriptors for Motion Detection from Aerial Videos, *ICPR*.
- [21] Liang, P., Teodoro, G., Ling, H., Blasch, E., Chen, G., Bai, L. (2012). Multiple Kernel Learning for Vehicle Detection in Wide Area Motion Imagery, *In: Int'l. Conf. on Info Fusion*, 2012.
- [22] Mitiche, A., Bouthemy, P. (1996). Computation and analysis of image motion: a synopsis of current problems and methods, *International Journal of Computer Vision*, 19 (1) 29-55, 1996.
- [23] Hu, W., Tan, T., Wang, L., Maybank, L. (2004). A survey on visual surveillance of object motion and behaviors, *IEEE Tr. on Systems, Man, and Cybernetics – Part C*, 34 (3) 334-352, August 2004.
- [24] Liu, K., Yang, H., Ma, B., Du, Q. (2010). A joint optical flow and principal component analysis approach for motion detection, *In: IEEE Int'l Conf. on Acoustics, Speech, and Signal Processing*, p 1178-1181, March.
- [25] Liu, K., Du, Q., Yang, H., Ma, B. (2010). Optical Flow and Principal Component Analysis-Based Motion Detection in Outdoor Videos, *EURASIP Journal on Advances in Signal Processing*, 2010.
- [26] Liu, K., Yang, H., Ma, B., Du, Q. (2011). Fast Motion Detection from Airborne Videos Using Graphics Computing Unit, *Journal of Applied Remote Sensing*, 6 (1) January 2011.
- [27] Mei, X., Ling, H., Wu, Y., *et al.* (2013). Efficient Minimum Error Bounded Particle Resampling L1 Tracker with Occlusion Detection, *IEEE Trans. on Image Processing (T-IP)*, 22 (7) 2661 – 2675.
- [28] Farneback, G. (2003). Two-Frame Motion Estimation Based on Polynomial Expansion, *In: Scandinavian Conf. on Image Analysis*, p. 363-370.
- [29] Lucas, B., Kanade, T. (1981). An iterative image registration technique with an application to stereo vision, *International Joint Conference on Artificial Intelligence*, p. 674-679, August.
- [30] Horn, B., Schunck, B. (1981). Determining optical flow, *Artificial Intelligence*, 17 (1-3) 185-203, 1981.
- [31] Horn, B., Schunck, B. (1993). Determining optical flow: a retrospective, *Artificial Intelligence*, 59 (1-2) 81-87.
- [32] Wu, R., Chen, Y., Blasch, E., Liu, B., *et al.* (2014). A Container-based Elastic Cloud Architecture for Real-Time Full-Motion Video (FMV) Target Tracking, *IEEE App. Imagery Pattern Rec. Workshop*.
- [33] Liu, B., Blasch, E., Chen, Y., Aved, A. J., Hadiks, A., Shen, D., Chen, G. (2014). Information Fusion in a Cloud Computing Era: A Systems-Level Perspective, *IEEE Aerospace and Electronic Systems Magazine*, 29 (10) 16 – 24, October.
- [34] Blasch, E., BiBona, P., Czajkowski, M., Barry, K., *et al.* (2014). Video Observations for Cloud Activity-Based Intelligence (VOCABI), *IEEE National Aerospace and Electronics (NAECON)*.
- [35] Menzel, M., Ranjan, R. (2012). CloudGenius: decision support for web server cloud migration, *ACM International Conference on World Wide Web*, p. 979-988, New York, NY, (April).